

MANUAL ALARM STATION

1MF1A / 1MI1A / 2ME1A / 2MH1A








1MF1A with 1MI1-06
2ME1A with 1MI1-06



1MF1A
2ME1A



1MI1A with 1MI1-06
2MH1A with 1MI1-06



Ordering Information

Model Name	Description
1MF1A	Manual Alarm Station c/w Telephone Jack w/o Surface Mount Box
1MI1A	Manual Alarm Station Outdoor type, c/w Telephone Jack, w/o Surface Mount Box
2ME1A	Manual Alarm Station w/o Telephone Jack w/o Surface Mount Box
2MH1A	Manual Alarm Station Outdoor type, w/o Telephone Jack, w/o Surface Mount Box
1MI1-06	Surface Mount Box for Manual Alarm Station

Specifications

Specifications	1MF1A	1MI1A	2ME1A	2MH1A	1MI1-06
Class	Class 1	Class 1	Class 2	Class 2	Surface Box
Installation Location	Indoor	Outdoor	Indoor	Outdoor	N/A
Telephone Jack	Available		N/A		N/A
Contact Capacity	250 mA @ 30VDC				N/A
Operation Lamp	Red LED	Red LED	N/A	N/A	N/A
Compatible Control Panel	1PE, PF, PK, PM, PN, PQ, PS, PV		2P1, C, D, H, K, 2PF2		N/A
Operating Temperature	-10°C to +50°C	-20°C to +70°C	-10°C to +50°C	-20°C to +70°C	N/A
Main Material	Flame-Retardant Resin				SPCC t1.2
Finish Color	Munsell 7R 4/13 (Red)				
Weight	200 g	250 g	200 g	250 g	450 g
Surface Mount Box	1MI1-06				N/A
Recessed Mount Box	JIS C 8340				N/A